





UHD image quality, new visual upgrade

With UHD resolution, the display achieves exceptional clarity and exquisite detail.

The kiosk delivers high brightness and contrast for accurate colour representation, faithfully reproducing every real detail.



Ambient light sensor

The automatic light sensor system adjusts the screen brightness according to the ambient light and colour temperature, which keeps the screen brightness for a comfortable viewing experience, saves energy and prolongs the service life.

IP65 super protection, robust and stable

The advertising kiosk is equipped with high-quality cooling fans and offers protection against lightning, overload, overvoltage, filtering, and over-temperature. Its structure includes waterproof and dustproof features, achieving an IP65 protection rating, allowing normal operation in various harsh environments.



3D surround sound system, immersive audiovisual experience

With a dual-channel surround sound amplifier system, it provides a seamless and immersive audio experience. The powerful low-frequency sound unit synchronizes with the visuals, delivering a stunning audiovisual presentation.



Remote control system, cloud-based intelligent management

Support various functions such as controlling display content, scheduling power on/off, and remote information publishing through mobile phones and computers, enabling remote management.

Support infrared remote control for menu selection, file playback, etc.

Powerful performance, stable output

With high stability and low failure rate, it supports continuous 24/7 operation, delivering uninterrupted and outstanding performance.

Application scenarios

Outdoor media advertising, bus stop signage, commercial square, scenic area signage, outdoor bulletin board.











SPECIFICATIONS

Model	KO55LCDVA-FSFP	KO55LCDVA-FDFP	KO65LCDVA-USFP	KO65LCDVA-UDFP	KO75LCDVA-USFP	KO75LCDVA-UDFP	KO86LCDVA-USFP	KO86LCDVA-UDFP
Resolution	1920*1080	1920*1080	3840*2160	3840*2160	3840*2160	3840*2160	3840*2160	3840*2160
Actual Screen Dimensions	55" (Single-sided)	55" (Double-sided)	65" (Single-sided)	65" (Double-sided)	75" (Single-sided)	75" (Double-sided)	86" (Single-sided)	86" (Double-sided)
Overal Dimensions (W x H x D mm)	848*2100*255	980*2150*300	1024*2350*235	1050*2300*300	1208*2600*255	1208*2500*320	1310*2852*300	1366*2700*330
Contrast Ratio	1200:1							
Chroma(M)	16.7M							
Brightness(nits)	2500 (Up to 4000)							
System	Android							
IP Rate	IP65							
Viewing Angle(H./V.)	178°/178°							
Working Voltage	100~240V, 50/60Hz							
Power Consumption	400	800	550	1100	1200	2400	1300	2500
Operating Temp(°C)	-20 ~ 50							
Humidity Range(%RH)	10~90							