


55" / 65" / 75" / 86"


LCD Education All-in-One

Android 11.0 | 178° VIEWING ANGLE | UHD




Wireless screen casting, unlimited sharing

Support mobile phones, tablets, computers and other terminals to cast screens wirelessly across systems, allowing up to 4 screens to be displayed simultaneously.



Anti-glare tempered glass

With 4mm high-strength anti-glare toughened glass, it effectively reduces scratches from long-term use, resists the effects of high light exposure in the conference environment and gives you a high-definition and detailed display.



Smart writing at your fingertips

Support two pens writing at the same time with a two-colour display, making it easier for multiple people to collaborate. Support convenient operations such as gesture erasure and drag-and-drop navigation, effectively improving meeting efficiency.

20points Infrared touch	±1mm Writing precision	≤3mm Writing height
-----------------------------------	----------------------------------	-------------------------------



Ultra-narrow bezel, streamlined look

Ultra-narrow bezel design with a display ratio of 85%. The front ports are integrated into the bezel for a simple and extraordinary all-in-one design.




Scan the QR code to share content

The content written on the whiteboard can be shared by scanning the QR code with your mobile phone, by email, or saved locally for next time.



Split-screen multitasking

Support for dual-screen displays and parallel task operation allows for a wider range of application scenarios.



Dual systems for diverse applications

Comes with Android 11.0 and the optional addition of Windows, providing more application options for conference usage.

SPECIFICATIONS

Model	SR55LCDVA-U	SR65LCDVA-U	SR75LCDVA-U	SR86LCDVA-U
Panel Size	55"	65"	75"	86"
Backlight Category	DLED			
Bare Dimension(W x H x Dmm)	1263 x 776.8 x 87.6	1484.6 x 903.08 x 87.21	1706.76 x 1027.32 x 87.31	1952.96 x 1167.77 x 87.18
Power Consumption(W)	330	400		550
Speakers Power	2*16W			
System	Android 11.0			
Optimum Resolution	3840*2160			
Viewing Angle	178°			
Brightness(cd/m²)	350			
Contrast Ratio	1200:1			
Response Time(ms)	8			
Operating Voltage	100 ~ 240V, 50/60Hz			
Operating Temp(°C)	-10 ~ 50			
Humidity Range(%RH)	10 ~ 80			
Front Port	USB3.0 x 2			
Input/Output	HDMI IN x 2,OPTICAL OUT x 2,USB3.0 x 1,USB2.0 x 1,TOUCH x 1,VGA IN x 1,AUDIO IN x 1,MIC IN x 1,RS232 x 1,RJ45 IN x 1,LINE OUT x 1			