

65"/ 75"/ 86"/ 98"/ 110"

LCD Conference All-in-One

Android 11.0 | FRONT TYPE-C PORT | UHD

Wireless screen casting, unlimited sharing
Support mobile phones, tablets, computers and other terminals to cast screens wirelessly across systems, allowing up to 4 screens to be displayed simultaneously.

Anti-glare tempered glass
With 3mm high-strength anti-glare toughened glass, it effectively reduces scratches from long-term use, resists the effects of high light exposure in the conference environment and gives you a high-definition and detailed display.

Smart writing at your fingertips

Support two pens writing at the same time with a two-colour display, making it easier for multiple people to collaborate. Support convenient operations such as gesture erasure and drag-and-drop navigation, effectively improving meeting efficiency.

20points

Infrared touch

±1mm

Writing precision

≤3mm

Writing height

Ultra-narrow bezel, streamlined look

Ultra-narrow bezel design with a display ratio of 85%. The camera and microphone are integrated into the bezel for a simple and extraordinary all-in-one design.

Clear sound pickup & HD video recording

Built-in 6-array microphone and 1300W/4800W pixel autofocus camera, picking up every word clearly and restoring the conference environment in real-time.

Split-screen multitasking

Support for dual-screen displays and parallel task operation allows for a wider range of application scenarios.

Dual systems for diverse applications

Comes with Android 11.0 and the optional addition of Windows, providing more application options for conference usage.

SPECIFICATIONS

Model	SR65LCDVB-U	SR75LCDVB-U	SR86LCDVB-U	SR98LCDVB-U	SR110LCDVB-U
Panel Size	65"	75"	86"	98"	110"
Backlight Category	DLED				
Bare Dimension(W x H x Dmm)	1488 x 906 x 87	1709 x 1029 x 88	1957 x 1169 x 88	2217 x 1331 x 104	2500 x 1507 x 106
Power Consumption(W)	400		550		850
Speakers Power	2*15W			2*16W	
System	Android 11.0				
Optimum Resolution	3840*2160				
Viewing Angle	178°				
Brightness(cd/m ²)	350				440
Contrast Ratio	1200:1				
Response Time(ms)	8				
Camera	Built-in 1300W pixel camera			Built-in 4800W pixel camera	
Operating Voltage	100 ~ 240V, 50/60Hz				
Operating Temp(°C)	-10 ~ 50				
Humidity Range(%RH)	10 ~ 80				
Front Port	HDMI IN x 1,USB3.0 x 2, TOUCH OUT x 1,TYPE-C x 1				
Input/Output	HDMI IN x 2,HDMI OUT x 1,USB2.0 x 1,USB3.0 x 2,TOUCH x 1,VGA IN x 1, AUDIO IN x 1,AUDIO OUT x 1,SPDIF x 1,RS232 x 1,RJ45 OUT x 1,RJ45 IN x 1			HDMI IN x 2,HDMI OUT x 1,USB2.0 x 1,USB3.0 x 2, TOUCH x 1,DP IN x 1,EARPHONE x 1,RS232 x 1, RJ45 OUT x 1,RJ45 IN x 1,COAX x1,MIC x 1	