



# Superior picture quality,

superb color performance

The all-in-one display employs flip-chip COB technology, savingenergy while being gentle on the eyes. With DCI-P3 wide color gamut and 1,000,000:1 contrast ratio, it delivers seamless colourtransitions and reproduces every detail.

DCI-P3 Color Gamut

**1,000,000:1** Contrast Ratio

#### All-in-one design, one display meets all needs

Built-in Android 11.0 system

Octa-core processor

Equipped with various input and output ports

Dual-channel surround sound

External cameras, microphones and other devices

can be connected

#### **Dual Operating System(op**

Windows/Android free switch









### High-precision touch control, inspiration at your fingertips

Supports touch control (compatible with dual systems) using highly precise infrared touch technology. Touch accuracy of ±2mm ensuresflexible and accurate interactive operations, enabling natural andsmooth writing for more convenient and efficient meetings.

#### Versatile screen mirroring,

#### built-in professional meeting software

- > Supports wireless screen mirroring for multiple platforms such as Windows, Mac OS, iOS, and Android, displaying up to four screens simultaneously.
- > Comes with a meeting whiteboard, video conference and other software, and users can install additional apps as needed.



## Multiple display modes, adaptive for all scenarios

Tailored for different meeting environments, offering Standard, Soft, Cinema, and Video modes for optimal display in any setting.





# Flexible installation,

#### easy maintenance

- > Support wall mounting and mobile stand-mounting.
- > Full front maintenance design allows for convenient installation and service.



#### **SPECIFICATIONS**

Model	S108COBVT-FSN	SR108COBVT-FSN	S135COBVT-FSN	SR135COBVT-FSN	S163COBVT-FSN	SR163COBVT-FSN	S216COBVT-USN
Display Size	108"	108"	135"	135"	163"	163"	216"
Resolution	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	3840*2160
Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9	16:9
Touch Control	No	Infrared touch	No	Infrared touch	No	Infrared touch	No
Overal Dimensions (W x H x Dmm)	2410 x 1480 x 31 Bottom Thickness 47	2423 x 1487 x 45 Bottom Thickness 47	3010 x 1817.5 x 31 Bottom Thickness 47	3023 x 1824 x 45 Bottom Thickness 47	3610 x 2155 x 31 Bottom Thickness 47	3623 x 2161 x 45 Bottom Thickness 47	4810 x 2830 x 31 Bottom Thickness 47
Actual Screen Dimensions(W x Hmm)	2400 x 1350	2400 x 1350	3000 x 1687.5	3000 x 1687.5	3600 x 2025	3600 x 2025	4800 x 2700
Installation Method	Mobile Stand / Wall Mounting						Wall Mounting
Refresh Rate(Hz)	3840						
Brightness(nits)	600						
Gray Scale(Bit)	22						
Contrast Ratio	1,000,000 : 1						
Viewing Angle(H./V.)	160° / 160°						
Maintenance Method	Front						
Operating System	Android 11.0, 8+128G						
Working Voltage	AC: 100V - 240V, 50/60 Hz						
Power Consumption Max(W)	1200	1200	1850	1850	2450	2450	4600
Power Consumption Avg.(W)	400	400	620	620	820	820	1550
Storage Temp.(°C)				-20 ~ 60			
Operating Temp.(°C)				-10 ~ 50			
Storage Humidity (%RH)	10 ~ 90						
Operating Humidity (%RH)				10 ~ 80			