

70"

COB

# V-Sight Air

## Indoor Advertising Kiosk

### Magnetic Splicing, Efficient Cascading

The magnetic trims and quick-lock design enable efficient cascading and splicing for instant large-screen displays.

Magnetic Trims



Multi-Unit Splicing



### IP65 Protection, Stable and Durable

The front side of the modules is IP65-rated for water, dust, and impact resistance.



### 8mm Ultra-Slim Trims, Immersive Visuals

8mm



8mm

### COB TrueColor, Brilliance in Every Pixel

Full flip-chip COB technology delivers wide color gamut, high contrast ratio, and uniform black levels.

#### DCI-P3

Wide Color Gamut

#### 1,000,000:1

High Contrast Ratio



### Full Front Maintenance



## Cloud Connection, Wireless Control

Users can use a variety of terminal devices, such as PCs, mobile phones, and tablets, to uniformly control multiple advertising kiosks through a wireless network for programme delivery, screen control, and other operations.



USB



HDMI IN



SPEAKER



HDMI OUT



## Blending Into One, More Than Just Display

With built-in speakers, the advertising kiosk requires no external audio equipment and has multiple types of signal ports to meet different application scenarios.

## SPECIFICATIONS

Model	KU70COBVB-12SCP (1)	KU70COBVB-15SCP (1)	KU70COBVB-12SNP (1)	KU70COBVB-15SNP (1)
Panel Technology	COB	COB	COB	COB
Pixel Pitch(mm)	P1.25	P1.5625	P1.25	P1.5625
Resolution	480*1350	384*1080	480*1350	384*1080
Actual Screen Dimensions(W x Hmm)	600 x 1687.5			
Overall Dimensions(WxH x Dmm)	616 x 1862.1 x 35.1 (490)			
Weight(kg)	45			
Brightness(nits)	600			
Viewing Angle(H./V.)	170°/170°			
Color Temperature(K)	2500~10000 (Adjustable)			
Gray Scale(bit)	14			
Refresh Rate(Hz)	3840			
Working Voltage	AC:100~240V, 50/60Hz			
Power Consumption Max(W)	≤320	≤330	≤320	≤330
Power Consumption Avg(W)	≤110	≤110	≤110	≤110
Operating Temp(°C)	-10~50			
Humidity Range(%RH)	10~80			
Display Mode	Synchronous/ Asynchronous			